



Pane 1	PLANICLEAR (4 mm) COOL-LITE SKN 176 II
Cavity 1	ARGON (90%) / AIR (10%) / 20 mm
Pane 2	PLANICLEAR (4 mm)

Regency Glass Ltd
Steven Massey
Leigh

07970 137136
stevemassey@regencyglass.co.uk

 **LUMINOUS FACTORS** CIE (15-2004)

Light transmission (TL %)	70 %
Outdoor reflection (RLe %)	13 %
Indoor (RLi %)	15 %

 **SOLAR FACTORS** EN410 (2011-04)


Solar factor (g)	0.37
Shading Coefficient (SC)	0.43

 **COLOR RENDERING** CIE (15-2004)

Transmission (Ra)	94.3
Reflection (Ra)	83.3

 **BURGLAR RESIST** EN356

Result :	NPD
----------	-----

 **ENERGY FACTORS** EN410 (2011-04)

Transmission (Te)	35 %
Reflection (Ree)	36 %
Indoor (Rei)	42 %
Absorption (AE1)	27 %
Absorption (AE2)	1 %

 **THERMAL TRANSMISSION** EN673 (2011-04)

Ug	1.1 W/m ² .K
0° related to vertical position	

 **MANUFACTURING SIZES**

Nominal thickness	28.0 mm
Weight	20 kg/m ²

 **PENDULUM RESISTANCE** EN12600

Result :	NPD
----------	-----

 **ACOUSTICS** EN12758

Acoustic simulated values	Rw(C;Ctr) = 30(-1;-5) dB
---------------------------	--------------------------